

Page 1/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Tel.: +49 (0)800 4372522

1 Identification

- · Product identifier
 - Trade name: Flexitime Xtreme 2 Correct flow base

· Application of the substance / the mixture Dental impression material

· Details of the supplier of the safety data sheet Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

Emergency telephone number:

Emergency CONTACT (24-Hour-Number) ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard identification

Classification of the substance or mixture

Carcinogenicity - Category 1A Reproductive Toxicity - Category 2

Specific Target Organ Toxicity - Repeated

Exposure - Category 1

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- · Label elements
 - GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Cristobalite

octamethylcyclotetrasiloxane

· Hazard statements

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

(Contd. on page 2)



Page 2/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system

· NFPA ratings for USA (scale 0-4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-Ratings (Scale 0-4)



Health = *0 Fire = 1 Reactivity = 0

· Other hazards -

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
 - · Description: -

· Dangero	· Dangerous components:		
14464-46-1	Cristobalite Carcinogenicity - Category 1A, H350; Specific Target Organ Toxicity - Repeated Exposure - Category 1, H372	25-50% w/w *	
27306-78-1	modified heptamethyltrisiloxane with polyalkylene oxide Acute Toxicity (Inhalation) - Category 4, H332; Eye Irritation - Category 2A, H319	0-5% w/w *	
556-67-2	octamethylcyclotetrasiloxane Flammable Liquids - Category 3, H226 Reproductive Toxicity - Category 2, H361 PBT; vPvB	≥0,1-<0,2% w/w *	

- * Actual concentration ranges are withheld as a trade secret.
- · Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of complaints.
 - After skin contact If skin irritation continues, consult a doctor.
 - After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

Information for doctor

· Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Page 3/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: Mount respiratory protective device.
- Additional information -

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid contact with eyes and skin.

- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
 - · Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Page 4/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

14464-46-1 Cristobalite

EL TWA: 0,025 mg/m³

respirable, ACGIH A2; IARC 1

EV TWA: 0,05* mg/m³ *respirable fraction

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

Personal protective equipment

General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

· Breathing equipment: Not required.

Protection of hands:

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

· Eye protection: Safety glasses

· Body protection: Light weight protective clothing

9 Physical and chemical properties

General Information		
· Appearance: · Form:	Pasty	
· Color:	Light green	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
· Melting point/Melting range:	undetermined	
· Boiling point/Boiling range:	2.230 °C (3630 °F)	
· Flash point:	>130 °C (>266 °F)	
· Flammability (solid, gaseous)	Not applicable.	
· Decomposition temperature:	Not determined.	

(Contd. on page 5)



Page 5/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

	(Contd. of page
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard. Not determined.
· Explosion limits:	
·Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density:	Not determined
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/v	vater): Not determined.
· Viscosity:	
· dynamic:	Not determined.
· kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: none
- · Additional information: -

11 Toxicological information

Information on toxicological effects
Acute toxicity:

l	· LD/	LC50 valu	es that are relevant for classification:			
ſ	556-67-2 octamethylcyclotetrasiloxane					
ſ	Oral	LD50	1.700 mg/kg (mouse)			
			4.800 mg/kg (rat)			
	Dermal	LD50	>2.400 mg/kg (rat)			
l	Inhalative	LC50/4 h	36 mg/l (rat)			

- Primary irritant effect:
 - · on the skin: No irritant effect. · on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

 Additional toxicological information: Harmful
 - · Carcinogenic categories
 - · IARC (International Agency for Research on Cancer)

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough,

(Contd. on page 6)



Page 6/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 5)

shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop mycobacterial infections (tuberculous and non-tuberculous) and fungal infections. Inhalation of air with a very high concentration of respirable silica dust can cause the most serious forms of silicosis in a matter of months or a few years. Some epidemiologic studies have concluded that there is significant risk of developing silicosis even at airborne exposure levels that are equal to the recommended NIOSH REL, the ACGIH TLV.

Cancer Status: The International Agency for Research on Cancer has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1 - carcinogenic to humans). Refer to IARC Monograph 100C, A Review of Human Carcinogens: Arsenic, Fibres and Dusts (published in 2011) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the Twelth Report on Carcinogens (2011). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

14464-46-1 Cristobalite

1

· NTP (National Toxicology Program)

14464-46-1 Cristobalite

Κ

· Reproductive toxicity Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
 - Aquatic toxicity: No further relevant information available.
- · Persistence and degradability

556-67-2 octamethylcyclotetrasiloxane

biodegradability 3,7 % (not defined)

- · Behavior in environmental systems:
 - · Bioaccumulative potential

556-67-2 octamethylcyclotetrasiloxane

Biokonzentrationefaktor (BCF) 12,4 (fish)

- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· Results of PBT and vPvB assessment

· PBT

556-67-2 octamethylcyclotetrasiloxane

· vPvB:

556-67-2 octamethylcyclotetrasiloxane

Other adverse effects No further relevant information available.

CΛ



Page 7/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

Void	
Void	
Void	
Void	
No	
Not applicable.	
II of Not applicable.	
-	
Void	
	Void Void Void No Not applicable. Il of Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - · Sara
 - · SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 8)



Page 8/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 11/17/2022

Reviewed on 11/17/2022

Trade name: Flexitime Xtreme 2 Correct flow base

(Contd. of page 7)

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Date of the latest revision of the safety data sheet 11/17/2022

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.